

SERIE DUNE



D.DUNE109+
D.DUNE09

D.DUNE112+
D.DUNE12

D.DUNE118+
D.DUNE18

D.DUNE124+
D.DUNE24

Alimentation					
Capacité nominale	Btu/kW	9000 (3207~11260)/2,6	12000 (3140~13000)/3,4	18000 (4263~20153)/5,1	24000 (6240~26598)/6,8
Puissance absorbée	W	825(240~1380)	1130(290~1500)	1580(330-2340)	2257(410~2824)
Intensité absorbée	A	4.0(1.2~8.0)	5.8(1.5~9.0)	8.1(1.7~12.0)	10.7(2.3~12.3)
EER					
Capacité nominale	Btu/kW	9200 (3207~11465)/2,7	12000 (3140~12992)/3,4	18000 (4263-20699)/5,1	24000 (6308-26936)/6,9
Puissance absorbée	W	699(240~1552)	922(290~1720)	1374(340-2520)	2063(420~3005)
Intensité absorbée	A	3.8(1.2~9.0)	5.1(1.5~10.0)	7.0(1.7~13.0)	9.9(2.3~13.5)
COP					
Capacité en froid	kW	2,6	3,4	5,1	6,8
SEER/Classe Énergétique		6,1/A++	6,1/A++	6,1/A++	6,1/A++
Capacité en chauffage	kW	2,0	2,1	3,8	4,8
SCOP/Classe Énergétique		4,0/A+	4,0/A+	4,0/A+	4,0/A+
Unité intérieure					
Portée d'air max. Raffr./Chauff.	m3/h	420	550	800	980
Niv Press.Sonore (Turbo/Haut/Med/Bas/Mute)	dB(A)	40/37/33/25/22	40/37/33/25/22	43/41/38//35/27	44/41/38/34/30
Dimension (LxhxP)	mm	698x255x190	777x250x201	910x294x206	1010x315x220
Poids net/total	Kg	6,5/8,5	8/10,5	10/13	13/16
Unité extérieure					
Niv. Press.Sonore/Puissance Sonore	dB(A)	50/60	50/60	55/65	57/67
Dimension (LxhxP)		765x310x481	765x310x481	890x628x385	960x732x400
Poids net/total	Kg	24/27	24/27	35/39	40/46
Refrigerant					
Type/GWP/Quantité préchargé		R32/675/0,57Kg	R32/675/0,57Kg	R32/675/1Kg	R32/675/1,14Kg
Liaison frigorifique					
Tube liquide/tube gaz	Pouce	3/8"-1/4"	3/8"-1/4"	3/8"-1/4"	1/2"-1/4"
Longueur Max./dénivelé	m	25/10	25/10	25/10	25/10